



# STABUMAX 500

## ANTI-SLIP FLOOR MAT

### COMPOSITION

- ▶ Anti-slip coating (top side)
- ▶ Board
- ▶ Anti-slip coating (bottom side)

### QUALITY OF PRODUCT

- ▶ Aggressive non-slip/ Very high coefficient of friction
- ▶ Easy to use / Save man hours during loading procedures
- ▶ Thickness does not influence height of skid
- ▶ **100% recyclable**

### APPLICATION USE

- ▶ Cargo securement anti-slip floor mats in transports, trains and containers
- ▶ Stowing option to increase product stability on floor bed
- ▶ Reduces the strapping required
- ▶ Successful for all product goods : pallets, over-sized cargo, paper rolls...

### PALLETIZATION

- ▶ Standard pallet sheet sizes (1000 sheets/pallet)
- ▶ Custom sheet sizes available

## SPECIFICATION SHEET

Paper type	Recycled board			Standards
Weight	500 g/sqm			ISO 536
Slide angle	Stabumax on Paper	Standard	Stabumax on wooden pallet	N/A
	≥ 65°	NF Q 03-083	N/A	
Static coefficient of friction	≥ 2	ISO 8295	≥ 0,9	VDI 2700-14
Dynamic coefficient of friction	≥ 0,6	ISO 8295	≥ 0,5	VDI 2700-14



TECHNICOAT  
*Solution*

solution@cgp-coating.com - www.cgp-coating.com

