RAVAS-2100


Pallet truck scale with multirange graduation













RAVAS-2100

FUNCTIONS

- Automatic and manual zero correction
- Gross/net weighing
- Automatic and manual tare up to 200 kg
- Totalling with sequence number
- Error messages in display
- Automatic switch-off after 30 minutes of non-use
- Low battery indication 5 hours before battery is empty

STANDARD SPECIFICATIONS

Weighing capacity

Graduation

Keypad

Battery

Protection class

2,200 kg

multirange:

0 - 200 kg: graduation 0.2 kg 200 - 500 kg: graduation 0.5 kg 500 - 2,200 kg: graduation 1 kg

0.1% of the load lifted

Max. tolerance

Display LCD, digit height 18 mm

3 function keys, on/off key

load cells IP67, indicator IP65

12Vdc/1.2Ah, exchangeable;

battery charger included

Battery life 35 hours, low battery indication 5 hours before automatic switch-off

Charger 230V/12Vdc - 300 mA

Charging time approximately 6 hours

Steering wheels rubber

Loading wheels polyurethane, single

Pump quick lift Own weight 99 kg

Colour red (RAL 3000), epoxy painted

For approved versions, class OIML III: European approval no. T2782, switch-off of display when tilting more than 2°. Graduation: multirange 0.5/1 kg, or one of the following fixed graduations:

- 1.000 divisions :1.0/1,000 kg or 2.0/2,000 kg - 2.000 divisions : 0.5/1,000 kg or 1.0/2,000 kg : 0.1/300 kg or 0.2/600 kg - 3,000 divisions

PREMIUM OPTIONS*

Bluetooth or WLAN output


Built-in thermal printer

Extra exchangeable battery pack

Legal for trade version, OIML III

or 0.5/1,500 kg

DIMENSIONS IN MM



Α	Fork length	1150
В	Fork width	170
С	Minimum fork height	87
	Space underneath fork	22
D	Maximum fork height	205
	Lifting height	120
Е	Width over forks	540
F	Height to top indicator	770







OPTIONS*

- Multirange graduation 0.1/0.2/0.5 kg
- Stainless steel fork shoes
- Stainless steel or galvanized truck
- Footbrake or handbrake
- Fork lengths: 950 2,500 mm
- Width over forks 700 mm
- Capacity 3,000 kg (graduation 1 kg)

* The use of options may change related specifications.

RAVAS UK Ltd

Office 130, 5 High Street Maidenhead, Berkshire, GB-SL6 1JN, United Kingdom T. +44 (0)1628 67 35 24, F. +44 (0)1628 67 08 78 info.uk@ravas.com, www.ravas.co.uk



rs LFT RAVAS-2100 EN UK rev.11.08.23 Changes