

# AUTOMATIC BATTERY WASHER

Protect your investment in your batteries with a SACKETT BATTERY WASHER with its unique NEUTRALIZING CYCLE. Regular washing and neutralizing of your batteries reduces or eliminates terminal and cable corrosion, as well as dirt and trash build-up on the battery tops.

All models incorporate the same wash, unique neutralize, rinse and blow-off systems. They vary only in the method used to move the batteries in and out of the washer



## GENERAL SPECIFICATIONS FOR ALL MODELS

- Stainless steel cabinet with epoxy primer
- Machine mounted electrical panel
- NEMA IV Push Buttons
- 1/2" port for in-plant water connection
- Limit Switch to prevent spray with door open
- Adjustable Blow Off Air Manifold  
(system supplied by in-plant compressed air)  
operates at 90 lbs. minimum, at 150 scfm of free air
- Panel Class II, UL approved
- 24 Volt Controls, NEC

## ROLLERS

- Model "A" Only: 1/4" thick polyethylene sleeve on 2 3/8" diameter. rollers with sealed ball bearings.
- Model "B" & "C" Only: 3 1/2" OD powered rollers with 3/8" polyethylene sleeve & 1 1/2" axle on a flange bearing externally mounted.

## Model "A"

- (designed primarily for use with a Hydra-Handler)
- Single Powered Door
- (7) Gravity rollers 2 3/8" diameter., 1/4" extruded coated
- 120v, 1ph, 24 volt control
- AC amp draw 3 amp, 15 amp branch
- Adjustable battery stop

## Model "B"

- (designed for use with HydraHandler or Transfer Cart with push/pull plate)
- Single Powered Door
- (7) Powered Rollers 3 1/2" diameter., 1/4" extruded coated
- 230/460v, 60hz, 3ph
- AC amp draw 8 amp @ 230 or 4 amp @ 460
- PLC Controlled

## Model "B+"

- (1) Powered Infeed, Outfeed Conveyor  
Same specifications as Model "B"



**SACKETT**  
Lifting, Stacking, Storing  
INNOVATING SINCE 1897

1033 Bryn Mawr Ave. • Bensenville • IL • 60106 • USA  
630.766.5500 • fax 630.766.5631 • [www.sackettsystems.com](http://www.sackettsystems.com)

# AUTOMATIC BATTERY WASHER

Model A



Model B



Model A-Over/Under



**Battery Size:** Max=46L x 40W x 31H with 20' Covers

**Construction:** 304 Stainless Steel

**Electrical:** UL listed control panel

Allen Bradley Controlled

Model "A": 115v, 1 phase, 60 hrz, 1 amp

**Water:** Approx. 7 gal/cycle, 45 psi min., 15 gpm min., 3/4" inlet.

**Air:** 90 psi., 150 SCFM min., 3/4" inlet



**SACKETT**  
Lifting, Stacking, Storing  
INNOVATING SINCE 1897

1033 Bryn Mawr Ave. • Bensenville • IL • 60106 • USA  
630.766.5500 • fax 630.766.5631 • [www.sackettsystems.com](http://www.sackettsystems.com)

© 2014 Sackett Systems ABW0714